

Idaho Transportation Department
Percent of MADT At Continuous Count Speed Sites

| | | | |
|------------------------|------------------------------------|------------------------|-----|
| Site ID: | 002150 003.960 | Scheme ID: | 6 |
| Location: | #110 SH-69 2.2 Miles North of Kuna | County: | ADA |
| Axle Factor Group: | 3 | Growth Factor Group: | 3 |
| Seasonal Factor Group: | 2 | FHWA Functional Class: | 6 |
| | | Speed Limit: | 55 |

| SPEED | 1999 Traffic Year | | | | | | | | | | | | |
|----------|-------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
| | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec | Avg |
| 0>-30 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.6 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 |
| 30>-35 | 0.3 | 0.3 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.5 | 0.1 | 0.1 | 0.1 | 0.3 | 0.2 |
| 35>-40 | 0.6 | 0.7 | 0.2 | 0.3 | 0.3 | 0.3 | 0.3 | 0.8 | 0.3 | 0.3 | 0.3 | 0.7 | 0.4 |
| 40>-45 | 1.6 | 1.6 | 1.1 | 1.3 | 1.5 | 1.2 | 1.1 | 1.9 | 1.3 | 1.3 | 1.3 | 2.2 | 1.5 |
| 45>-50 | 5.8 | 5.8 | 5.6 | 6.7 | 7.6 | 6.0 | 5.3 | 6.5 | 5.9 | 6.0 | 6.4 | 8.2 | 6.3 |
| 50>-55 | 26.7 | 25.5 | 26.8 | 28.4 | 30.7 | 28.4 | 27.3 | 26.5 | 26.8 | 27.5 | 28.2 | 28.9 | 27.7 |
| 55>-60 | 44.5 | 45.4 | 46.5 | 45.8 | 43.9 | 45.6 | 45.7 | 43.8 | 45.9 | 45.8 | 45.4 | 43.7 | 45.2 |
| 60>-65 | 17.2 | 17.2 | 16.6 | 14.9 | 13.5 | 15.7 | 17.2 | 16.3 | 16.8 | 16.3 | 15.4 | 13.4 | 15.9 |
| 65>-70 | 2.6 | 2.8 | 2.5 | 2.1 | 1.8 | 2.2 | 2.4 | 2.6 | 2.4 | 2.1 | 2.3 | 2.1 | 2.3 |
| 70>-75 | 0.4 | 0.4 | 0.4 | 0.3 | 0.3 | 0.3 | 0.4 | 0.4 | 0.4 | 0.3 | 0.3 | 0.3 | 0.4 |
| 75>-80 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 |
| 80>-85 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 85>-140 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| AVG SPD | 56.3 | 56.4 | 56.5 | 56.1 | 55.8 | 56.2 | 56.5 | 55.9 | 56.4 | 56.3 | 56.2 | 55.6 | 56.2 |
| 50% SPD | 56.7 | 56.8 | 56.7 | 56.4 | 56.1 | 56.5 | 56.7 | 56.5 | 56.7 | 56.6 | 56.5 | 56.1 | 56.5 |
| 85% SPD | 61.5 | 61.6 | 61.4 | 60.8 | 60.3 | 61.1 | 61.5 | 61.4 | 61.4 | 61.2 | 61.0 | 60.3 | 61.2 |
| %EXCD 55 | 64.8 | 65.9 | 66.1 | 63.2 | 59.6 | 63.9 | 65.8 | 63.3 | 65.5 | 64.7 | 63.5 | 59.6 | 63.8 |
| %EXCD 60 | 20.3 | 20.5 | 19.6 | 17.4 | 15.7 | 18.3 | 20.1 | 19.5 | 19.6 | 18.9 | 18.1 | 15.8 | 18.7 |
| %EXCD 65 | 3.1 | 3.3 | 3.0 | 2.5 | 2.2 | 2.6 | 2.9 | 3.2 | 2.8 | 2.6 | 2.7 | 2.5 | 2.8 |
| %EXCD 70 | 0.5 | 0.5 | 0.5 | 0.4 | 0.4 | 0.5 | 0.5 | 0.5 | 0.5 | 0.4 | 0.4 | 0.4 | 0.5 |
| %EXCD 75 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 |
| %EXCD 80 | 0.0 | 0.0 | 0.0 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| %EXCD 85 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| | 6,886 | 7,249 | 7,445 | 7,278 | 7,216 | 7,946 | 7,813 | 7,585 | 7,859 | 7,888 | 7,601 | 7,638 | |